

### **AMENDMENTS TO THE CLAIMS**

The listing of claims will replace all prior versions, and listings, of claims in the application.

#### **Listing of Claims**

1. (Currently Amended) An active matrix substrate, comprising:  
first bus lines and second bus lines arranged to form a matrix;  
switching devices provided near respective intersections of the first bus lines and the second bus lines; and  
pixel electrodes electrically connected to the first bus lines and the second bus lines through the switching devices, wherein:  
at least one of the first bus lines has a first capacitance formed thereon, ~~and~~  
the first bus lines, except for the at least one first bus line with a first capacitance, are connected to first bus lines on another active matrix substrate, and  
the first capacitance is formed by arranging (i) a first bus line not connected to first bus lines on another active matrix substrate and (ii) a line other than the second bus lines to cross each other.

2. (Original) The active matrix substrate as set forth in claim 1, wherein  
the at least one first bus line with a first capacitance is connected to a line connected to no pixel electrode on the other active matrix substrate.

3. (Original) The active matrix substrate as set forth in claim 1, wherein  
each of those first bus lines which have no first capacitance formed thereon has a second  
capacitance formed thereon which is less than the first capacitance.

4. (Original) The active matrix substrate as set forth in claim 1, wherein  
the first bus lines are connected to a source driver, and the second bus lines are connected  
to a gate driver.

5. (Original) The active matrix substrate as set forth in claim 1, wherein  
the first bus lines are connected to a gate driver, and the second bus lines are connected to  
a source driver.

6. (Currently Amended) A display, comprising an active matrix substrate including:  
first bus lines and second bus lines arranged to form a matrix;  
switching devices provided near respective intersections of the first bus lines and the  
second bus lines; and

pixel electrodes electrically connected to the first bus lines and the second bus lines  
through the switching devices, wherein:

at least one of the first bus lines has a first capacitance formed thereon, ~~and~~  
the first bus lines, except for the at least one first bus line with a first capacitance, are  
connected to first bus lines on another active matrix substrate, and

the first capacitance is formed by arranging (i) a first bus line not connected to first bus lines on another active matrix substrate and (ii) a line other than the second bus lines to cross each other.

7. (Currently Amended) A display, comprising display panels each including an active matrix substrate including:

first bus lines and second bus lines arranged to form a matrix;

switching devices provided near respective intersections of the first bus lines and the second bus lines; and

pixel electrodes electrically connected to the first bus lines and the second bus lines through the switching devices, wherein:

at least one of the first bus lines has a first capacitance formed thereon, ~~and~~

the first bus lines, except for the at least one first bus line with a first capacitance, are shared for use among the active matrix substrates in the display panels, and

the first capacitance is formed by arranging (i) a first bus line that is on an active matrix substrate and that is not shared for use with another active matrix substrate and (ii) a line other than the second bus lines to cross each other.

8. (Original) The display as set forth in claim 7, wherein

the first bus lines shared among the display panels each have a second capacitance formed thereon which is less than the first capacitance.

9. (Original) The display as set forth in claim 7, further comprising a source driver and a gate driver for applying a signal voltage to the first bus lines and the second bus lines, wherein the first bus lines are connected to the source driver, and the second bus lines are connected to the gate driver.

10. (Original) The display as set forth in claim 7, further comprising a source driver and a gate driver for applying a signal voltage to the first bus lines and the second bus lines, wherein the first bus lines are connected to the gate driver, and the second bus lines are connected to the source driver.

11. (Original) The display as set forth in claim 7, wherein one of the display panels is designated as a main panel, and the display panels, except for the main panel, are designated as sub-panels having less display pixels than the main panel.

12. (Currently Amended) A display, comprising display panels each including an active matrix substrate including:

first bus lines and second bus lines arranged to form a matrix;  
switching devices provided near respective intersections of the first bus lines and the second bus lines; and  
pixel electrodes electrically connected to the first bus lines and the second bus lines through the switching devices, wherein:  
the first bus lines are shared for use among the display panels;

in at least one of the display panels, at least one of the first bus lines is connected to none of the pixel electrodes on the active matrix substrate, ~~and~~

the at least one first bus line connected to none of the pixel electrodes has a first capacitance formed thereon, and

the first capacitance is formed by arranging (i) a first bus line not connected to the pixel electrodes and (ii) a line other than the second bus lines to cross each other.

13. (Original) The display as set forth in claim 12, wherein  
each of those first bus lines which have no first capacitance formed thereon has a second capacitance formed thereon which is less than the first capacitance.

14. (Original) The display as set forth in claim 12, further comprising a source driver and a gate driver for applying a signal voltage to the first bus lines and the second bus lines, wherein

the first bus lines are connected to the source driver, and the second bus lines are connected to the gate driver.

15. (Original) The display as set forth in claim 12, further comprising a source driver and a gate driver for applying a signal voltage to the first bus lines and the second bus lines, wherein

the first bus lines are connected to the gate driver, and the second bus lines are connected to the source driver.

16. (Original) The display as set forth in claim 12, wherein  
one of the display panels is designated as a main panel, and the display panels, except for  
the main panel, are designated as sub-panels having less display pixels than the main panel.

17. (Previously presented) The active matrix substrate as set forth in claim 1, wherein  
an amount of the first capacitance is such that there is substantially no difference in signal  
delay on each first bus line of the active matrix substrate that is connected to a first bus line on  
the other active matrix substrate and signal delay on the at least one first bus line with a first  
capacitance.

18. (Previously presented) The display as set forth in claim 6, wherein  
an amount of the first capacitance is such that there is substantially no difference in signal  
delay on each first bus line of the active matrix substrate that is connected to a first bus line on  
the other active matrix substrate and signal delay on the at least one first bus line with a first  
capacitance.

19. (Previously presented) The display as set forth in claim 7, wherein  
an amount of the first capacitance is such that there is substantially no difference in signal  
delay on each first bus line that is shared for use among the active matrix substrates in the  
display panels and signal delay on the at least one first bus line with a first capacitance.

20. (Previously presented) The display as set forth in claim 12, wherein  
an amount of the first capacitance is such that there is substantially no difference in signal  
delay on each first bus line that is shared for use among the display panels and signal delay on  
the at least one the first bus line with a first capacitance.